

Application No. 09/735,762  
Filed: December 13, 2000  
Group Art Unit: 1746

AMENDMENT TO THE CLAIMS

1. - 11. (Canceled)

1 12. (Original) A method of operating a dry-cleaning system,  
2 comprising:

3 disposing substrates to be dry-cleaned into a cleaning  
4 vessel;

5 evacuating air and water vapor from the interior of the  
6 cleaning vessel to the atmosphere;

7 equalizing the pressure between a first storage vessel  
8 containing a dry-cleaning medium and the cleaning vessel;

9 conveying the dry-cleaning medium from a second storage  
10 vessel to the cleaning vessel;

11 agitating the substrates in the cleaning vessel;

12 conveying liquid dry-cleaning medium from the cleaning vessel  
13 to the second storage vessel;

14 evacuating gaseous dry-cleaning medium from the cleaning  
15 vessel to the first storage vessel; and

16 raising the cleaning vessel internal pressure to atmospheric  
17 pressure by admitting air.

1 13. (Original) The method of claim 12, wherein equalizing the  
2 pressure comprises selectively operating a compressor and valves  
3 associated with conduits interconnecting the first storage vessel  
4 and the cleaning vessel.

1 14. (Original) The method of claim 12, wherein conveying the dry-  
2 cleaning medium comprises selectively operating a compressor and

Application No. 09/735,762

Filed: December 13, 2000

Group Art Unit: 1746

3 valves associated with conduits interconnecting the second storage  
4 vessel and the cleaning vessel.

Sub B2  
1 15. (Original) The method of claim 12, wherein conveying liquid  
2 dry-cleaning medium comprises selectively operating a compressor  
3 and valves associated with conduits interconnecting the second  
4 storage vessel and the cleaning vessel.

1 16. (Original) The method of claim 12, wherein evacuating gaseous  
2 dry-cleaning medium comprises selectively operating a compressor  
3 and valves associated with conduits interconnecting the first  
4 storage vessel and the cleaning vessel.

AI  
1 17. (Original) The method of claim 12, wherein agitating  
2 comprises agitating the substrates in the cleaning vessel through  
3 rotation of a rotatable basket disposed within the cleaning  
4 vessel.

1 18. (Original) The method of claim 12, wherein evacuating gaseous  
2 dry-cleaning medium further comprises conducting the gaseous dry-  
3 cleaning medium through a heat exchanging conduit disposed within  
4 the cleaning vessel.

1 19. (Original) The method of claim 12, wherein evacuating gaseous  
2 dry-cleaning medium further comprises conducting the gaseous dry-  
3 cleaning medium through an aperture into a lower portion of the  
4 first storage vessel to enable heat transfer from the gaseous dry-  
5 cleaning medium to dry-cleaning medium already disposed in the  
6 first storage vessel.